



SPECIFICATIONS

MAX # OF CARTRIDGES: 22 (Ø2 1/2)

MATERIAL: CS, SS (TYPE 304, 316...), EXOTIC ALLOYS, OR OTHER ON REQUEST

CONNECTION TYPES:

FLANGE: RFSO, RFWN #150;

COUPLING: FNPT#3000; MNPT#3000;
SANITARY TRI-CLAMP

DRAIN CONNECTION: 1" FNPT#3000 2 PLC'S.

VENT CONNECTION: 1/4" FNPT#3000 ON LID

GAUGE CONNECTION: 1/4" FNPT#3000 ON LID

DESIGN PRESSURE: 150PSI, OR PER REQUEST

DESIGN TEMPERATURE: 250°F, OR PER REQUEST

GASKET: BUNA-N, EPR/EPDM, TEVC, VITON, OR OTHER ON REQUEST

CARTRIDGE TYPES: DOUBLE OPEN END
222 TYPE O-RING
OR OTHER ON REQUEST

THREE LEGS WITH BOLT DOWN HOLES Ø1"

| CARTRIDGE LENGTH | A | B | C | D | E | F | INLET/OUTLET CONNECTION SIZE |
|------------------|----|----|--------|----|--------|--------|------------------------------|
| 10 | 25 | 53 | 35 1/2 | 16 | 26 1/2 | 7 | 2 |
| 20 | 25 | 63 | 44 | 16 | 26 1/2 | 8 1/2 | 3 |
| 30 | 25 | 74 | 44 | 16 | 26 1/2 | 18 1/2 | 4 |
| 40 | 25 | 83 | 44 | 16 | 26 1/2 | 27 | 4 |

NOTES: SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE
ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING;