

# Y-TYPE STRAINERS

## MODELS & SPECIFICATIONS



### Y600CS & Y600SS **OPERATING PRESSURES AND TEMPERATURES**

**Model Y600CS / Y600SS**

**Steam: 600psig @ 838°F**

**600psig @ 1125°F**

**Water, oil, gas:**

**1480psig @ 100°F**

**1440psig @ 100°F**

Size	A	B	C	Blow-off	Wt. Lb.
1-1/2	12-3/4	8-3/4	13	1/2	37
2	13-3/4	8-7/8	14	1/2	48
2-1/2	16	10-5/8	17	3/4	64
3	17-3/4	11-7/8	18	1	83
4	21	15-1/4	24	1-1/2	182
5	24	17-1/4	26	2	302
6	29	20-1/4	32	2	389
8	34-5/8	23-1/4	36	2	596
10	38-1/2	27-1/4	41	2	906
12	44-1/4	31-1/8	48	2	1130
14	47-1/4	33-1/8	50	2	1350
16	53	37-3/4	56	2	1850
18	58-1/2	41-5/8	63	3	2205
20	62-1/2	45	68	3	2800
24	70-1/2	51	76	3	4025

**NOTES:** SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE  
ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING



385 Watline Avenue, Mississauga, Ontario, L4Z 1P3