



### SPECIFICATIONS

**MAX # OF CARTRIDGES:** 8 (Ø2 1/2)

**MATERIAL:** CS, SS (TYPE 304, 316...), EXOTIC ALLOYS, OR OTHER ON REQUEST

**CONNECTION TYPES:**

FLANGE: RFSO, RFWN #150;

COUPLING: FNPT#3000; MNPT#3000;  
SANITARY TRI-CLAMP

**DRAIN CONNECTION:** 1" FNPT#3000 2 PLC'S.

**VENT CONNECTION:** 1/4" FNPT#3000 ON LID

**GAUGE CONNECTION:** 1/4" FNPT#3000 ON LID

**DESIGN PRESSURE:** 150PSI, OR PER REQUEST

**DESIGN TEMPERATURE:** 250°F, OR PER REQUEST

**GASKET:** BUNA-N, EPR/EPDM, TEVC, VITON, OR OTHER ON REQUEST

**CARTRIDGE TYPES:** DOUBLE OPEN END  
222 TYPE O-RING  
OR OTHER ON REQUEST

**THREE LEGS WITH BOLT DOWN HOLES Ø5/8"**

CARTRIDGE LENGTH	A	B	C	D	E	F	INLET/OUTLET CONNECTION SIZE
10	16 5/8	46	34	10 3/4	27	4 3/4	2
20	16 5/8	56	44	10 3/4	27	8 1/2	3
30	16 5/8	66	44	10 3/4	27	18	3
40	16 5/8	76	44	10 3/4	27	28	4

NOTES: SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE  
ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING;