



### SPECIFICATIONS

**MAX # OF CARTRIDGES: 6 (Ø2 1/2)**

**MATERIAL:** CS, SS (TYPE 304, 316...), EXOTIC ALLOYS, OR OTHER ON REQUEST

**CONNECTION TYPES:**

FLANGE: RFSO, RFWN #150;  
 COUPLING: FNPT#3000; MNPT#3000;  
 SANITARY TRI-CLAMP

**DRAIN CONNECTION:** 1" FNPT#3000 2 PLC'S.  
**VENT CONNECTION:** 1/4" FNPT#3000 ON LID  
**GAUGE CONNECTION:** 1/4" FNPT#3000 ON LID  
**DESIGN PRESSURE:** 150PSI, OR PER REQUEST  
**DESIGN TEMPERATURE:** 250°F, OR PER REQUEST

**GASKET:** BUNA-N, EPR/EPDM, TEVC, VITON, OR OTHER ON REQUEST

**CARTRIDGE TYPES:** DOUBLE OPEN END  
 222 TYPE O-RING  
 OR OTHER ON REQUEST

**THREE LEGS WITH BOLT DOWN HOLES Ø5/8"**

CARTRIDGE LENGTH	A	B	C	D	E	F	INLET/OUTLET CONNECTION SIZE
10	16 5/8	46	34	6 5/8	27	8 1/2	2
20	16 5/8	56	44	6 5/8	27	8 1/2	2
30	16 5/8	66	44	6 5/8	27	18	2
40	16 5/8	76	44	6 5/8	27	28	2

**NOTES:** SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE  
 ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING;