

FABRICATED STRAINERS

MODELS & SPECIFICATIONS



DIMENSIONAL DATA

FB150CS & FB150SS OPERATING PRESSURES AND TEMPERATURES

Model FB150CS / FB150SS

Steam: 150psig @ 567°F / 150psig @ 567°F

Water, oil, gas:

287psig @ 100°F / 275psig @ 100°F

Size	Body Size	A	B	C	D	Blow-off	Wt. Lb.
1-1/2	3-1/2	8	9-1/2	4-1/2	8	1/2	20
2	3-1/2	18	12-7/8	6-1/2	8-1/8	1/2	27
2-1/2	4-1/2	19	14-1/2	7-1/2	8-3/4	3/4	34
3	4-1/2	22	15-1/2	8	9-7/8	3/4	48
4	6-5/8	25	17-3/4	9	11-1/2	1	78
5	6-5/8	27	19-3/8	10	13-1/8	1	90
6	8-5/8	30	22-1/8	12-1/2	14-7/8	1-1/4	140
8	10-3/4	37	30-1/8	19	18-11/16	1-1/2	300
10	12-3/4	46	34-3/4	21	20-1/8	1-1/2	430
12	14	52	37-5/8	22	26-1/4	2	720
14	16	56	40-5/8	23-1/2	30-1/4	2	1010
16	18	59	44-1/8	25-1/2	33-1/8	2	1300
18	20	65	48-1/8	28	38-3/8	3	1965
20	24	70	53-5/8	32	41-1/2	3	2600
24	30	80	62-7/8	38	41-1/2	3	4000

FB300CS & FB300SS OPERATING PRESSURES AND TEMPERATURES

Model FB300CS / FB300SS

Steam: 300psig @ 838°F / 300psig @ 1138°F

Water, oil, gas:

740psig @ 100°F / 720psig @ 100°F

Size	Body Size	A	B	C	D	Blow-off	Wt. Lb.
1-1/2	3-1/2	10	10-3/8	4-1/2	8-1/4	1/2	35
2	3-1/2	20	13-3/8	6-1/2	8-3/8	1/2	37
2-1/2	4-1/2	21	14-3/4	7-1/2	9	3/4	49
3	4-1/2	24	16-1/4	8	10-1/4	1	75
4	6-5/8	27	18-7/8	9	12-1/8	1-1/2	118
5	6-5/8	29	20-3/4	10	14	2	148
6	8-5/8	32	23-7/8	12-1/2	15-7/8	2	225
8	10-3/4	39	32-1/4	19	20-1/16	2	425
10	12-3/4	48	36-7/8	21	21-1/2	2	600
12	14	54	39-3/4	22	27-5/8	2	930
14	16	58	43-1/8	23-1/2	31-3/4	2	1400
16	18	61	46-5/8	25-1/2	34-5/8	2	1700
18	20	67	51-1/4	28	40	3	2450
20	24	73	56-7/8	32	43-1/4	3	3300
24	30	83	66-3/4	38	43-3/8	3	5280

NOTES: SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE
ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING



385 Watline Avenue, Mississauga, Ontario, L4Z 1P3