

# FABRICATED STRAINERS

## MODELS & SPECIFICATIONS



### **FB600CS & FB600SS OPERATING PRESSURES AND TEMPERATURES**

Model FB600CS / FB600SS

Steam: 600psig @ 838°F / 600psig @  
1125°F

Water, oil, gas:

1480psig @ 100°F / 1440psig @ 100°F

Size	Body Size	A	B	C	D	Blow-off	Wt. Lb.
1-1/2	3-1/2	11	10-1/2	5-1/2	8-1/4	1/2	42
2	3-1/2	21	13-5/8	6-3/4	8-5/8	1/2	64
2-1/2	4-1/2	22	15	7-3/4	9-1/4	3/4	75
3	4-1/2	25	16-1/2	8-1/2	10-1/2	3/4	110
4	6-5/8	28	19-1/2	9-1/2	12-5/8	1	205
5	6-5/8	30	22-1/2	10-1/2	14-3/4	1	325
6	8-5/8	34	25-3/8	13	16-3/4	1-1/4	490
8	10-3/4	41	34-1/8	20	21-3/16	1-1/2	750
10	12-3/4	51	39-3/8	22	22-3/4	1-1/2	1040
12	14	57	41-3/4	23	28-7/8	2	1330
14	16	61	44-3/4	25	31-1/2	2	1780
16	18	64	48-7/8	26	38-1/8	2	2460
18	20	71	53-5/8	30	41-3/4	3	3200
20	24	77	59-5/8	34	45-1/4	3	4280
24	30	88	69-3/4	40	45-7/8	3	6500

**NOTES:** SPECIFICATION AND SIZES CAN CHANGE WITHOUT PRIOR NOTICE; FOR REFERENCE ONLY; NOT TO BE USED FOR PRE-PIPING WORK; NOT TO SCALE  
ACCURATE DIMENSIONS AND DETAILS WILL BE ISSUED WITH ENGINEERING DRAWING



385 Watline Avenue, Mississauga, Ontario, L4Z 1P3